

DESCRIPTION



Normet SSL 15 pump is a mixing unit mounted onto a rotor-stator pump for the application of TamCrete SSL. The pump is electrical driven, available for different voltage and needs compressed air for the nozzle system.

Normet SSL 15 has a mechanical gear box to adjust the output of the rotor stator.

TECHNICAL DATA

Normet SSL 15	
Dimensions	
Length	1200 mm
Width	700 mm
Loading Height	1200 mm
Weight	± 120 kg
Output	Up to 1 m ³ /h
Aggregate Size	Up to 4 mm
Outlet	25 mm / 32 mm

Conveying Distance

Horizontally	Up to 100 m - material dependent
Vertically	Up to 15 m

Air Requirements

4 - 6 bar @ 11 m³/min (60 - 90psi @ 400 c.f.m) on air motor drive

Fittings / Hoses

15 m 1 inch to be used for slurry with Normet SSL 15 nozzle

15 m ½ inch for air and accelerator supply

Dosing

Peristaltic dosing pump, 4 l/min at 50Hz, 16 bar maximum

Options

Electric Drive - 4kW. 380/525v on pump and mixer, adjustable to local demand

Hydraulic Drive (optional to electric drive)

SSL 15 Nozzle (standard)

HEALTH & SAFETY

Normet SSL 15 should only be used as directed. Our recommendations for protective equipment should be strictly adhered to for your personal protection.